



1,500 / 1,800 user
30,000 / 100,000 transaction
Option: ID, HID, Mifare card, Wi-Fi,
Hardware platform ZEM 500



Model : **Bravo 8**

ID/HID/Mifare Card, Webserver, Antipass-back



50 time zones



Standalone Fingerprint and Card Access Control System

ACCESS CONTROL

Bravo 8 is a widely used Access Control in the office. Choosing a lot of stable original parts, strictly follow the national security product standard. Bravo 8 is suitable for the entrances and exits of office, factory, hotel, school, etc. All input /output are using anti-jamming protection and over-voltage/circuit protection. The product experiences the strict degradation test before leaving factory. The greatest advantage of Bravo 8 is easy to install, with multifunctional & elegant design and reasonable price.



Connects with world-class management, pro-motes management improvement



Certified of ISO 9001 : 2000



"We are the leader of fingerprint solution "

Standalone Fingerprint and Card Access Control System

(Connection)



FEATURE

- Hardware platform: ZEM500
- Operating system: Linux
- User capacity: 1500
- Transaction capacity: 50000
- Sensor: Optical CMOS Sensor
- Algorithm version 2007 Version ZK new algorithm
- Access Control: 50 Time Zone, 5 Grouping, 10 Combination, Holiday Management, support many fingerprints access, support standalone work
- Communicational: TCP/IP or RS232 and RS485
- Keyboard and Display: LCD with 80 character and figure keypad
- Power: 12 V
- Identification speed: <=2 seconds
- Language: simplified Chinese, traditional Chinese, English, other Languages
- Standard: Wire Doorbell, Wiegand OUT, Wiegand IN
- Optional: ID/HID/Mifare card, Webserver, USB host, Short message, Workcode, RIS, Antipass-back
- Optional: Webserver, Workcode, RIS, Multi-identification, 9 Digits User ID, Schedule Status, T&A Records.

TECHNICAL SPECIFICATION

Size	98.5 (L) x 56 (W) x 180 (H) mm.
Hardware platform	ZEM500
Operating system	Linux
User capacity:	1,500/2,800
Transaction capacity:	50,000/100,000
Sensor:	Optical CMOS
Access Control:	50 Time Zone, 5 Grouping, 10 Combination, Holiday Management, support many fingerprints access, support standalone work
Communicational:	TCP/IP or RS232 , RS485 and USB
Keyboard and Display:	LCD with 80 character and figure keypad
Power:	12 V
Identification speed:	<=2 seconds
FRR:	<=1%
FAR:	<=0.0001%
Temperature operating:	0°C - 45°C
Humidity operating:	20%-80%
Language:	English, Thai
Standard:	Wire Doorbell, Wiegand OUT, Wiegand IN
Optional:	ID/HID/Mifare card, Webserver, USB host, Short message, Workcode, Antipass-back
Optional:	Webserver, Workcode, RIS, Multi-identification, 9 Digits User ID, Schedule Status, T&A Records.

